APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date	of filing in State Engineer's Office
Retu	rned to applicant for correction
Corr	ected application filed
Мар	filed
	The applicant Willow Glen Water Co.
	Las Vegas , County of Clark , Nevada
	of Nevada , hereby make application for permission to appropriate the public
	if a copartnership or association, give names of members.) See remarks
	if a copartnership or association, give names of memoers.)
	The source of the proposed appropriation is <u>Underground - Las Vegas</u> Name of stream, lake or other source.
	Artesian Basin
2.	The amount of water applied for is 0.0936 second-feet
	(a) If stored in reservoir give number of acre-feet
3.	The water to be used for Quasi-Municipal & Domestic (Subdivision)
4.	Irrigation, power, mining, manufacturing, domestic, or other use. If use is for:
	(a) Irrigation (state number of acres to be irrigated)
	(b) Stockwater (state number and kinds of animals to be watered)
	(c) Other use (describe fully under "No. 11. Remarks")
	(d) Power:
	(1) Horsepower developed
	(2) Point of return of water to stream
5.	The water is to be diverted from its source at the following point: within Gov't Lot #4, Sec.
I	T. 22 S., R. 62 E., M.D.B.&M., Nevada from which the NW Cor. of said Describe as being within a 40-acre subdivision of public survey, and by course and distance to a section corner. If on unsurveyed land, Sec. 6 bears N. 50° 38' 39" W., a distance of 1672.05 feet.
6.	it should be stated. Place of use 'A portion of Gov't Lot #4, Sec. 6, T. 22 S., R. 62 E.,
	Describe by legal subdivision, if on unsurveyed land it should be so stated. M.D.B.&M.', Nevada
7.	Use will begin about January 1st and end about December 31st , of each year.
8.	Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans
	and specifications of your diversion or storage works.) a drilled and cased well together
	With a pump, pressure tank distribution system. State manner in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits.

plicant Willow Glen Water Co. By s/ V. G. V. G.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
willow Glen Water Co. is a co-ownership com as shown on the attached certificate. plicant Willow Glen Water Co. Bys/ V. G. V. G. V. G. State APPROVAL OF STATE ENG This is to certify that I have examined the foregoing application, and conditions: ghts and is further subject to revocation if ranished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, near the point of diversion into must be kept of water placed to beneficinat this right must allow for a reasonable low ter level. The well shall be equipped with a surring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Enginesie erefore, the State retains the right to regulate the samount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
plicant Willow Glen Water Co. Bys/V. G. W. G. APPROVAL OF STATE ENGINEER APPROVAL OF STATE ENGINEER APPROVAL This is to certify that I have examined the foregoing application, and cowing limitations and conditions: This permit is issued ghts and is further subject to revocation if raished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion into must be kept of water placed to beneficing at this right must allow for a reasonable low ter level. The well shall be equipped with a surring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the cherein granted at any and all times.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measured in the n, and accurate measured al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
plicant Willow Glen Water Co. By S/ V. G. V. G. APPROVAL OF STATE ENGINEER APPROVAL OF STATE ENGINEER APPROVAL OF STATE ENGINEER APPROVAL This is to certify that I have examined the foregoing application, and owing limitations and conditions: ghts and is further subject to revocation if ranished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, near the point of diversion ints must be kept of water placed to beneficiate this right must allow for a reasonable low ter level. The well shall be equipped with a suring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the characteristic granted at any and all times.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure- al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
plicant Willow Glen Water Co. By S/ V. G. V. G. APPROVAL OF STATE ENGINEER APPROVAL OF STATE ENGINEER APPROVAL OF STATE ENGINEER APPROVAL This is to certify that I have examined the foregoing application, and owing limitations and conditions: ghts and is further subject to revocation if ranished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, near the point of diversion ints must be kept of water placed to beneficiate this right must allow for a reasonable low ter level. The well shall be equipped with a suring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the characteristic granted at any and all times.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
By s/V. G. W. G. Marked hs/jw dc/jb State APPROVAL OF STATE ENGINEERS This is to certify that I have examined the foregoing application, and covering limitations and conditions: This permit is issued only by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion in the must be kept of water placed to beneficial at this right must allow for a reasonable low ter level. The well shall be equipped with a surring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the remaining of the state and all times. The amount of water to be appropriated shall be limited to the amount which to exceed to exceed cubic feet per second.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
By s/V. G. W. G. Marked hs/jw dc/jb State APPROVAL OF STATE ENGINEERS This is to certify that I have examined the foregoing application, and covering limitations and conditions: This permit is issued only by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion in the must be kept of water placed to beneficial at this right must allow for a reasonable low ter level. The well shall be equipped with a surring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the remaining of the state and all times. The amount of water to be appropriated shall be limited to the amount which to exceed to exceed cubic feet per second.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
By s/V. G. W. G. Marked hs/jw dc/jb State APPROVAL OF STATE ENGINEERS This is to certify that I have examined the foregoing application, and covering limitations and conditions: This permit is issued only by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion in the must be kept of water placed to beneficial at this right must allow for a reasonable low ter level. The well shall be equipped with a surring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the remaining of the state and all times. The amount of water to be appropriated shall be limited to the amount which to exceed to exceed cubic feet per second.	Krametbauer Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understood wering of the static a 2-inch opening for ing, a valve must be
By s/ V. G. V. G. May a dc/jb APPROVAL APPROVAL This is to certify that I have examined the foregoing application, and coming limitations and conditions: This permit is issued to revocation if raished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, near the point of diversion into the management of diversion at this right must allow for a reasonable low ter level. The well shall be equipped with a suring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the control of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understoomering of the static a 2-inch opening for ing, a valve must be
APPROVAL OF STATE ENGINEERS APPROVAL OF STATE ENGINEERS APPROVAL OF STATE ENGINEERS APPROVAL OF STATE ENGINEERS AND CONTINUES APPROVAL OF STATE ENGINEERS AND CONTINUES APPROVAL OF STATE ENGINEERS AP	Krametbauer Water Right Surveyor #2 GINEER do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measure-al use. It is understoomering of the static a 2-inch opening for ing, a valve must be
APPROVAL OF STATE ENGINEERS APPROVAL OF STATE ENGINEERS OF STATE ENGIN	do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measureal use. It is understood wering of the static a 2-inch opening for ing, a valve must be
This is to certify that I have examined the foregoing application, and the same lowing limitations and conditions: This permit is issued lowing limitations and conditions: ghts and is further subject to revocation if rnished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, near the point of diversion into must be kept of water placed to beneficiate at this right must allow for a reasonable low ter level. The well shall be equipped with assuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate. Therein granted at any and all times. The amount of water to be appropriated shall be limited to the amount which to exceed to exceed cubic feet per second.	do hereby grant the same, subject to the subject to existing and when water can be tor a municipality installed in the n, and accurate measureal use. It is understood wering of the static a 2-inch opening for ing, a valve must be
This permit is issued lowing limitations and conditions: ghts and is further subject to revocation if rnished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion on the must be kept of water placed to beneficiate this right must allow for a reasonable lower level. The well shall be equipped with assuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the state of the same and all times. This permit is issued to revocation if revocation is revocation if revocation if revocation if revocation is revocation if revocation if revocation is revocation in revocation is revocation.	subject to existing and when water can be t or a municipality installed in the n, and accurate measure- al use. It is understoo wering of the static a 2-inch opening for ing, a valve must be
This permit is issued lowing limitations and conditions: ghts and is further subject to revocation if rnished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion on the must be kept of water placed to beneficiate this right must allow for a reasonable lower level. The well shall be equipped with assuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to regulate the state of the same and all times. This permit is issued to revocation if revocation is revocation if revocation if revocation if revocation is revocation if revocation if revocation is revocation in revocation is revocation.	subject to existing and when water can be t or a municipality installed in the n, and accurate measure- al use. It is understoo wering of the static a 2-inch opening for ing, a valve must be
owing limitations and conditions: ghts and is further subject to revocation if rnished by an entity such as a water distric gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion nts must be kept of water placed to beneficia at this right must allow for a reasonable low ter level. The well shall be equipped with a asuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Enginese erefore, the State retains the right to regulate the state is any and all times. e amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	and when water can be t or a municipality installed in the n, and accurate measureal use. It is understoomering of the static a 2-inch opening for ing, a valve must be
rnished by an entity such as a water district gaged in furnishing water. A meter must be scharge pipeline, hear the point of diversion on the must be kept of water placed to beneficiant this right must allow for a reasonable low ter level. The well shall be equipped with a suring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require the state retains the right to require amount of water to be appropriated shall be limited to the amount which to exceed	installed in the installed in the n, and accurate measure-al use. It is understoom wering of the static a 2-inch opening for ing, a valve must be
gaged in furnishing water. A meter must be scharge pipeline, near the point of diversion of must be kept of water placed to beneficiate this right must allow for a reasonable low ter level. The well shall be equipped with a suring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require the state retains the right to require the state and all times. The amount of water to be appropriated shall be limited to the amount which to exceed to exceed cubic feet per second.	installed in the n, and accurate measure- al use. It is understoo wering of the static a 2-inch opening for ing, a valve must be
nts must be kept of water placed to beneficiant this right must allow for a reasonable low ter level. The well shall be equipped with assuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require terminate granted at any and all times. The amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second.	al use. It is understoomering of the static a 2-inch opening for ing, a valve must be
nts must be kept of water placed to beneficiant this right must allow for a reasonable low ter level. The well shall be equipped with assuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require terminate granted at any and all times. The amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second.	al use. It is understoomering of the static a 2-inch opening for ing, a valve must be
ter level. The well shall be equipped with a asuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require terminating the remaining to the state and all times. The amount of water to be appropriated shall be limited to the amount which to exceed	wering of the static a 2-inch opening for ing, a valve must be
ter level. The well shall be equipped with a asuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require term granted at any and all times. The amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second.	a 2-inch opening for ing, a valve must be
asuring depth to water. If the well is flow stalled and maintained to prevent waste. The thin an area designated by the State Engineer erefore, the State retains the right to require terrherein granted at any and all times. The amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	ing, a valve must be
stalled and maintained to prevent waste. The thin an area designated by the State Enginee: erefore, the State retains the right to regulate the state and all times. The amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second.	,
thin an area designated by the State Engineer erefore, the State retains the right to regular termherein granted at any and all times. The amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	is source is located
erefore, the State retains the right to requirement of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	•
terrherein granted at any and all times. e amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	r pursuant to NRS 534.03
e amount of water to be appropriated shall be limited to the amount which to exceed 0.0936 cubic feet per second	late the use of the
to exceed 0.0936 cubic feet per second	
to exceed 0.0936 cubic feet per second	
	ch can be applied to beneficial use, and
	, but not to exceed
± 1117 to 1114	
tual construction work shall begin on or before	
oof of commencement of work shall be filed before	•
ork must be prosecuted with reasonable diligence and be completed on or	• • • • • •
oof of completion of work shall be filed before	
plication of water to beneficial use shall be made on or before	July 24, 1969
of of the application of water to beneficial use shall be filed on or before.	July 24, 1969 June 24, 1971
	July 24, 1969 June 24, 1971 July 24, 1971
p in support of proof of beneficial use shall be filed on or before	July 24, 1969 June 24, 1971 July 24, 1971
nmencement of work filed JULY 31, 1969 IN TESTIMONY WHEREOF	July 24, 1969 June 24, 1971 July 24, 1971 , I ROLAND D. WESTERGARD
nmencement of work filed ULY 31, 1969 IN TESTIMONY WHEREOF opletion of work filed ULY 31, 1969 State Engineer of Nevada	July 24, 1969 June 24, 1971 July 24, 1971 July 24, 1971 ROLAND D. WESTERGARD have hereunto set my hand and the seal of
nmencement of work filed ULV 31, 1969 IN TESTIMONY WHEREOF State Engineer of Nevada of of beneficial use filed. AUG 96, 1977 my office, this 24th	July 24, 1969 June 24, 1971 July 24, 1971 , I ROLAND D. WESTERGARD
nmencement of work filed ULY 31, 1969 IN TESTIMONY WHEREOF opletion of work filed ULY 31, 1969 State Engineer of Nevada	July 24, 1969 June 24, 1971 July 24, 1971 July 24, 1971 ROLAND D. WESTERGARD, have hereunto set my hand and the seal of day of March